

## **TB74 Protocol for RS232 104U / Pulse**

**IDR Support bill 1000, 2000, 5000, 10000, 20000, 50000, 100000 (Indonesia)**

### **DIP SW SETTING : 1**

| FUNCTION |                           | SW1                 | SW2 | SW3 | SW4 | SW5 | SW6 | SW7 | SW8 | SW9 | SW10 |
|----------|---------------------------|---------------------|-----|-----|-----|-----|-----|-----|-----|-----|------|
| ★        | 1 Pulse / IDR 1000        | OFF                 | OFF | OFF |     |     |     |     |     |     |      |
|          | 2 Pulse / IDR 1000        | OFF                 | OFF | ON  |     |     |     |     |     |     |      |
|          | 3 Pulse / IDR 1000        | OFF                 | ON  | OFF |     |     |     |     |     |     |      |
|          | 4 Pulse / IDR 1000        | OFF                 | ON  | ON  |     |     |     |     |     |     |      |
|          | 5 Pulse / IDR 1000        | ON                  | OFF | OFF |     |     |     |     |     |     |      |
|          | 10 Pulse / IDR 1000       | ON                  | OFF | ON  |     |     |     |     |     |     |      |
|          | 20 Pulse / IDR 1000       | ON                  | ON  | OFF |     |     |     |     |     |     |      |
|          | 100 Pulse / IDR 1000      | ON                  | ON  | ON  |     |     |     |     |     |     |      |
|          | Fast Output Pulse         | Lo=50ms<br>Hi=100ms |     |     | ON  |     |     |     |     |     |      |
| ★        | Slow Output Pulse         | Lo=50ms<br>Hi=300ms |     |     | OFF |     |     |     |     |     |      |
|          | Inhibit level Active Low  |                     |     |     |     | ON  |     |     |     |     |      |
| ★        | Inhibit level Active High |                     |     |     |     | OFF |     |     |     |     |      |
| ★        | Accept IDR 1000 & 2000    |                     |     |     |     |     | ON  |     |     |     |      |
|          | Reject IDR 1000 & 2000    |                     |     |     |     |     | OFF |     |     |     |      |
| ★        | Accept IDR 5000 & 10000   |                     |     |     |     |     |     | ON  |     |     |      |
|          | Reject IDR 5000 & 10000   |                     |     |     |     |     |     | OFF |     |     |      |
| ★        | Accept IDR 20000          |                     |     |     |     |     |     |     | ON  |     |      |
|          | Reject IDR 20000          |                     |     |     |     |     |     |     | OFF |     |      |
| ★        | Accept IDR 50000          |                     |     |     |     |     |     |     |     | ON  |      |
|          | Reject IDR 50000          |                     |     |     |     |     |     |     |     | OFF |      |
| ★        | Accept IDR 100000         |                     |     |     |     |     |     |     |     |     | ON   |
|          | Reject IDR 100000         |                     |     |     |     |     |     |     |     |     | OFF  |

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch.

### **DIP SW SETTING : 2**

| FUNCTION |                        | SW1 | SW2 | SW3 | SW4 |
|----------|------------------------|-----|-----|-----|-----|
| ★        | Pulse Normal High (NO) | ON  |     |     |     |
|          | Pulse Normal Low (NC)  | OFF |     |     |     |
| ★        | Pulse Protocol         |     | ON  |     |     |
|          | RS232 Protocol         |     | OFF |     |     |
|          | Reserved               |     |     | ON  |     |
| ★        | Reserved               |     |     | OFF |     |
|          | Reserved               |     |     |     | ON  |
| ★        | Reserved               |     |     |     | OFF |

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch