TB74 Protocol for RS232 104U / Pulse

TTD6 Support bill 1 、5 、10 、20 、50 、100 (Trinidad)

DIP SW SETTING : 1

	FUNCTION		SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / TTD 1		OFF	OFF								
	2 Pulse / TTD 1		OFF	ON								
	4 Pulse / TTD 1		ON	OFF								
	10 Pulse / TTD 1		ON	ON								
★	Output Pulse	Lo=50ms Hi=50ms			OFF	OFF						
	Output Pulse	Lo=50ms Hi=30ms			OFF	ON						
	Output Pulse	Lo=300ms Hi=60ms			ON	OFF						
	Output Pulse	Lo=150ms Hi=150ms			ON	ON						
	Inhibit level Active Low						ON					
★	Inhibit level Active High						OFF					
★	Accept TTD 1							ON				
	Reject TTD 1							OFF				
★	Accept TTD 5								ON			
	Reject TTD 5								OFF			
★	Accept TTD 10 & 20									ON		
	Reject TTD 10 & 20									OFF		
★	Accept TTD 50										ON	
	Reject TTD 50										OFF	
★	Accept TTD 100											ON
	Reject TTD 100											OFF

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch.

DIP SW SETTING : 2

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High (NO)	ON			
	Pulse Normal Low (NC)	OFF			
★	Pulse Protocol		ON		
	RS232 Protocol		OFF		
	Reserved			ON	
★	Reserved			OFF	
	Reserved				ON
★	Reserved				OFF

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch.