



# TP70P3B/P5 Protocol for RS232 104U / Pulse

BRC6 Support bill 2, 5, 10, 20, 50, 100 ( Brazil )

## DIP SW SETTING : 1

FUNCTION			SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / BRC 1		OFF	OFF								
	2 Pulse / BRC 1		OFF	ON								
	4 Pulse / BRC 1		ON	OFF								
	10 Pulse / BRC 1		ON	ON								
		<b>Note1</b>	<b>Note2</b>									
★	Output Pulse	Lo=50ms Hi=100ms			OFF	OFF						
	Output Pulse	Lo=150ms Hi=100ms			OFF	ON						
	Output Pulse	Lo=20ms Hi=100ms			ON	OFF						
	Output Pulse	Lo=30ms Hi=150ms			ON	ON						
	Inhibit level Active Low						ON					
★	Inhibit level Active High						OFF					
★	Accept BRC 2							ON				
	Reject BRC 2							OFF				
★	Accept BRC 5								ON			
	Reject BRC 5								OFF			
★	Accept BRC 10 & 20									ON		
	Reject BRC 10 & 20									OFF		
★	Accept BRC 50										ON	
	Reject BRC 50										OFF	
★	Accept BRC 100											ON
	Reject BRC 100											OFF

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch.

## DIP SW SETTING : 2

FUNCTION		SW1	SW2	SW3	SW4
★	Pulse Normal High (NO)	ON			
	Pulse Normal Low (NC)	OFF			
★	Pulse Protocol		ON		
	RS232 Protocol		OFF		
	2nd bill delay open			ON	
★	2nd bill delay close			OFF	
	Refer to Note 2				ON
★	Refer to Note 1				OFF

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch

Note 1	
Currency	Pulse
BRC 2	2
BRC 5	5
BRC 10	10
BRC 20	20
BRC 50	50
BRC 100	100

Note 2	
Currency	Pulse
BRC 2	2
BRC 5	3
BRC 10	4
BRC 20	5
BRC 50	6
BRC 100	7