



TP70P3B/P5 Protocol for RS232 004 / Pulse

CRC5 Support bill 1000, 2000, 5000, 10000, 20000 (CostaRica)

DIP SW SETTING : 1

FUNCTION		SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / CRC 1000	OFF	OFF	OFF							
	2 Pulse / CRC 1000	OFF	OFF	ON							
	3 Pulse / CRC 1000	OFF	ON	OFF							
	4 Pulse / CRC 1000	OFF	ON	ON							
	5 Pulse / CRC 1000	ON	OFF	OFF							
	10 Pulse / CRC 1000	ON	OFF	ON							
	20 Pulse / CRC 1000	ON	ON	OFF							
	100 Pulse / CRC 1000	ON	ON	ON							
	Fast Output Pulse	Lo=50ms Hi=100ms			ON						
★	Slow Output Pulse	Lo=50ms Hi=300ms			OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept CRC 1000						ON				
	Reject CRC 1000						OFF				
★	Accept CRC 2000							ON			
	Reject CRC 2000							OFF			
★	Accept CRC 5000								ON		
	Reject CRC 5000								OFF		
★	Accept CRC 10000									ON	
	Reject CRC 10000									OFF	
★	Accept CRC 20000										ON
	Reject CRC 20000										OFF

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch.

DIP SW SETTING : 2

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High (NO)	ON			
Pulse Normal Low (NC)	OFF			
★ Pulse Protocol		ON		
RS232 Protocol		OFF		
Straight			ON	
★ Turn Over			OFF	
Manufacture Default				ON
★ System Default				OFF

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch