



# TP70P3B/P5 Protocol for RS232 104U / Pulse

IDR4 Support bill 10000、20000、50000、100000 (Indonesia)

## DIP SW SETTING : 1

| FUNCTION                    | SW1      | SW2 | SW3 | SW4 | SW5 | SW6 | SW7 | SW8 | SW9 | SW10 |
|-----------------------------|----------|-----|-----|-----|-----|-----|-----|-----|-----|------|
| ★ 1 Pulse IDR 10000         | OFF      | OFF | OFF |     |     |     |     |     |     |      |
| ★ 2 Pulse IDR 10000         | OFF      | OFF | ON  |     |     |     |     |     |     |      |
| ★ 3 Pulse IDR 10000         | OFF      | ON  | OFF |     |     |     |     |     |     |      |
| ★ 4 Pulse IDR 10000         | OFF      | ON  | ON  |     |     |     |     |     |     |      |
| ★ 5 Pulse IDR 10000         | ON       | OFF | OFF |     |     |     |     |     |     |      |
| ★ 10 Pulse IDR 10000        | ON       | OFF | ON  |     |     |     |     |     |     |      |
| ★ 20 Pulse IDR 10000        | ON       | ON  | OFF |     |     |     |     |     |     |      |
| ★ 100 Pulse IDR 10000       | ON       | ON  | ON  |     |     |     |     |     |     |      |
| Fast Output Pulse           | Lo=50ms  |     |     | ON  |     |     |     |     |     |      |
|                             | Hi=100ms |     |     |     |     |     |     |     |     |      |
| ★ Slow Output Pulse         | Lo=50ms  |     |     | OFF |     |     |     |     |     |      |
|                             | Hi=300ms |     |     |     |     |     |     |     |     |      |
| Inhibit level Active Low    |          |     |     |     | ON  |     |     |     |     |      |
| ★ Inhibit level Active High |          |     |     |     | OFF |     |     |     |     |      |
| ★ Accept IDR 10000          |          |     |     |     |     | ON  |     |     |     |      |
| ★ Reject IDR 10000          |          |     |     |     |     | OFF |     |     |     |      |
| ★ Accept IDR 20000          |          |     |     |     |     |     | ON  |     |     |      |
| ★ Reject IDR 20000          |          |     |     |     |     |     | OFF |     |     |      |
| ★ Accept IDR 50000          |          |     |     |     |     |     |     | ON  |     |      |
| ★ Reject IDR 50000          |          |     |     |     |     |     |     | OFF |     |      |
| ★ Accept IDR 100000         |          |     |     |     |     |     |     |     | ON  |      |
| ★ Reject IDR 100000         |          |     |     |     |     |     |     |     | OFF |      |
| ★ Accept IDR Reserved       |          |     |     |     |     |     |     |     |     | ON   |
| ★ Reject IDR Reserved       |          |     |     |     |     |     |     |     |     | OFF  |

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch.

## DIP SW SETTING : 2

| FUNCTION                 | SW1 | SW2 | SW3 | SW4 |
|--------------------------|-----|-----|-----|-----|
| ★ Pulse Normal High (NO) | ON  |     |     |     |
| Pulse Normal Low (NC)    | OFF |     |     |     |
| ★ Pulse Protocol         |     | ON  |     |     |
| RS232 Protocol           |     | OFF |     |     |
| Straight                 |     |     | ON  |     |
| ★ Turn Over              |     |     | OFF |     |
| Reserved                 |     |     |     | ON  |
| ★ Reserved               |     |     |     | OFF |

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch