



TP70P3B/P5 Protocol for RS232 104U / Pulse

TTD6 Support bill 1, 5, 10, 20, 50, 100 (Trinidad)

DIP SW SETTING : 1

FUNCTION		SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / TTD 1	OFF	OFF								
	2 Pulse / TTD 1	OFF	ON								
	4 Pulse / TTD 1	ON	OFF								
	10 Pulse / TTD 1	ON	ON								
★	Output Pulse	Lo=50ms Hi=50ms		OFF	OFF						
	Output Pulse	Lo=50ms Hi=30ms		OFF	ON						
	Output Pulse	Lo=300ms Hi=60ms		ON	OFF						
	Output Pulse	Lo=150ms Hi=150ms		ON	ON						
	Inhibit level Active Low					ON					
★	Inhibit level Active High					OFF					
★	Accept TTD 1						ON				
	Reject TTD 1						OFF				
★	Accept TTD 5							ON			
	Reject TTD 5							OFF			
★	Accept TTD 10 & 20								ON		
	Reject TTD 10 & 20								OFF		
★	Accept TTD 50									ON	
	Reject TTD 50									OFF	
★	Accept TTD 100										ON
	Reject TTD 100										OFF

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch.

DIP SW SETTING : 2

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High (NO)	ON			
Pulse Normal Low (NC)	OFF			
★ Pulse Protocol		ON		
RS232 Protocol		OFF		
Straight			ON	
★ Turn Over			OFF	
Reserved				ON
★ Reserved				OFF

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch